

## Installation of Wood Cornices

## **Inside Mount**



inside mounting brackets

## **Outside Mount**



outside mount brackets

Attach small section of L bracket (supplied with order) to the rear face of the cornice (see diagram). Hold cornice in place at window while screwing the top of the L bracket into the top of the window frame.

The installation of the cornice for an inside mount installation must be done prior to installing any window blinds or shades.

Hold cornice in place over window blind to set the exact height of the cornice. Make a pencil mark where the dustcover meets the wall; this pencil mark will become the top of your cornice once mounted. Screw the L brackets to the wall so that the long side of the L bracket is touching the pencil mark and the small side is flush to the wall. Once the L brackets are in place and spaced evenly from left to right, lay the cornice on top of the L bracket setting the dustcover on top of the extended part

of the L bracket. Screw small <sup>1</sup>/<sub>2</sub>" wood screws from under the dust cover through the pre drilled holes in the L brackets. One screw per bracket is sufficient.

## It is our recommendation to install the L brackets for your cornice first then, install your window blind and last but not least install the cornice over the window blind or shade.

It is importance when following these instructions that the cornice and the L brackets extend <u>beyond</u> the front of the blind so that you can access the screw holes to secure the L bracket to the dustcover. L brackets can be adjusted to fit the inside depth of the cornice by breaking at the "score" lines provided. See photo for outside mount cornice for bracket placement.